



Why use UST Bond Tile Fixing Solutions?



Modern tiles are low absorbent (porosity <3%)



Without additives, a mix of sand-cement dries fast leading to early debonding.



Laying tiles traditionally with sand cement mix will create voids underneath, and makes the tiles fragile and develops cracks in the future.



Tile Adhesives are a mix of graded sand, cement, polymers, and additives specially formulated for the required combination of tiles & substrates



Additives provide water retention and sag resistance on vertical application.



Polymers provide cohesiveness allowing for even application with a trowel.

Features & Benefits



High Bond Strength
It has excellent adhesive properties and bonds better to substrate.



No Shrinkage
Shrinkage cracks are minimized/eliminated due to its water retaining and self-curing properties.



High Sag Resistance
No slip is observed on vertical applications.



Zero Wastage
It is easy to apply and avoids wastage of materials.



Extended Open Time
Specially added polymers impart extended open time, leading to higher flexibility at the time of application.



Economical & Time Saving:
It is applied in a thin layer which leads to cost saving & being premixed saves time.

Tile O Bond - TB 21

TILE O BOND - TOB 21: your ultimate solution for superior tile adhesion. Engineered with excellence in mind, TOB 21 offers exceptional strength and reliability, ensuring secure tile installations that stand the test of time. Suitable for a variety of applications. Trust TILE O BOND - TOB 21 to deliver superior tile adhesion, making it the preferred choice for professional contractors and DIY enthusiasts alike.

Suitable for

- Ceramic tile installations
- Porcelain tile installations
- Stone tile installations
- Mosaic tile installations
- Interior and exterior tile projects



Technical Specifications

Packaging Size: 20Kg & 40Kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	White Liquid	60-90 mins.	60-90 mins.	1.50 Mpa	1.50 Mpa	35-40 Sq.Ft	Type-4	C2 TE S2

Tile O Bond - TB 11

Tile O Bond - TB 11, your go-to solution for tile installation needs. Our grey tile adhesive is meticulously crafted to provide exceptional bonding strength, ensuring secure and long-lasting tile installations. Whether you're working with vitrified or ceramic tiles, Tile O Bond - TB 11 offers versatility and reliability, making it suitable for a wide range of applications. Trust in Tile O Bond - TB 11 to bring your tiling projects to life with ease and confidence.

Suitable for

a wide range of applications. Trust in Tile O Bond - TB 11 to bring your tiling projects to life with ease and confidence.



Technical Specifications

Packaging Size: 20Kg & 40Kg Bags

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg & 40kg bag)	IS 15477:2019	EN 12004
Specifications	Grey Powder	3-4 Hours	60 mins	2.50 N/mm ²	2.50 N/mm ²	35-40 Sq.Ft	Type -3	C2 TE S1



Tile O Bond - TB 27

The epitome of premium tile adhesive solutions. Crafted with meticulous attention to quality and performance, TB 27 offers unparalleled strength and reliability for your tiling projects

Suitable for

- Ceramic and porcelain tile installations
- Natural stone tile installations
- Large format tile installations
- High-traffic areas
- Interior and exterior tile projects

Technical Specifications

Packaging Size: 20 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	Grey/White powder	>60 mins	>20 mins.	0.50 Mpa	1.00 Mpa	35-40 Sq.Ft	Type-1	C1T



Tile O Bond - TB 31

TB 31: the epitome of premium tile adhesive solutions. Engineered with superior quality and performance in mind, TB 31 offers unmatched strength and reliability for your tiling projects.

Suitable for

- Ceramic and porcelain tile installations
- Natural stone tile installations
- Large format tile installations
- High-traffic areas
- Interior and exterior tile projects

Technical Specifications

Packaging Size: 20 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	Grey / White powder	>60 mins	>30 mins.	1.50 Mpa	1.50 Mpa	30-35 Sq.Ft	Type-3	C2 TE S1

Tile O Bond - TB 51

TILE O BOND Ultra - TOB 51: the epitome of platinum-grade tile adhesive. Crafted with precision and innovation, TOB 51 sets the standard for superior performance, providing unmatched strength and reliability for your tile installations

Suitable for

- A variety of applications
- Ceramic and porcelain tile installations
- Natural stone tile installations
- Large format tile installations
- High-traffic areas
- Wet areas and moisture-prone environments
- Interior and exterior tile projects



Technical Specifications

Packaging Size: 20 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	White Liquid	60-90 mins.	60-90 mins.	1.50 Mpa	1.50 Mpa	35-40 Sq.Ft	Type-4	C2 TE S2

Repair Mortar

A polymer modified cement-based adhesive for fixing large format tiles marble, granite, stones, and glass mosaic on floor and walls. It is suitable for both internal and external applications.

Suitable for

- Large format tiles on internal and external walls & Floors, Granite, Marble and other stones and Glass Mosaic
- Vitrified Tiles on interior & exterior Floor & Wall



Technical Specifications

Packaging Size: 25 Kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	Grey / White powder	>60 mins	>30 mins.	1.50 Mpa	1.50 Mpa	30-35 Sq.Ft	Type-3	C2 TE S1



Ready – Mix Plaster

Ready Mix Plaster - RMP 01: the ultimate solution for hassle-free plastering. Pre-mixed and ready to use, RMP 01 offers convenience and efficiency, saving you time and effort on your projects. With excellent coverage and a smooth finish, it ensures professional results every time. Say goodbye to the complexities of traditional plastering and embrace the simplicity of Ready Mix Plaster - RMP 01.

Suitable for

RMP 01 offers excellent adhesion, coverage, and workability, making it a versatile choice for various plastering needs.

Technical Specifications

Packaging Size: 40 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	Grey / White powder	>60 mins	>30 mins.	1 Mpa	1.25 Mpa	35-40 Sq.Ft	Type-1	C2T

Block Jointing Mortar



Jointing mortar: a dry mixed adhesive engineered to create robust bonds between blocks and various surfaces. Designed for reliability and strength, this adhesive ensures secure connections, making it ideal for a wide range of applications. From masonry to construction projects, trust our jointing mortar to deliver durable and professional-grade results, every time.

Suitable for

various applications, ensuring sturdy connections in construction projects, masonry work, and more. Trust our jointing mortar to deliver robust bonds, making it the go-to solution for your bonding needs.

Technical Specifications

Packaging Size: 40 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	Grey powder	>60 mins	>20 mins.	0.50 Mpa	1.00 Mpa	35-40 Sq.Ft	Type-1	C1T



Screed FS 100

The perfect solution for achieving a smooth and level surface effortlessly. Whether you're working on a flooring project or laying foundations, Screed FS 100 ensures a flat and even finish every time.

Suitable for

- Flooring installations
- Construction projects
- Renovation projects
- Roadworks and paving
- Industrial applications

Technical Specifications

Packaging Size: 20 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	White Liquid	60-90 mins.	60-90 mins.	1.50 Mpa	1.50 Mpa	35-40 Sq.Ft	Type-4	C2 TE S2



Dust Lok- Ultra

The ultimate solution for anti-dust wall protection. Specially formulated to combat dust accumulation on walls, Dust Lok-Ultra provides a long-lasting barrier that helps keep your walls clean and pristine. Experience the superior dust protection of Dust Lok- Ultra and enjoy cleaner, healthier walls in any setting. Suitable for a variety of applications

Suitable for

- Interior walls
- High-traffic areas
- Industrial environments
- Healthcare facilities
- Educational institutions

Technical Specifications

Packaging Size: 20 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	Grey / White powder	>60 mins	>30 mins.	1.50 Mpa	1.50 Mpa	30-35 Sq.Ft	Type-3	C2 TE S1



TILE BONDER

MagicBond -3X Tile Bonder is an onsite mix for improving the strength and workability of cement. Due to its high water retention property, when mixed with cement it enhances the bonding strength of mix by 3 times. It also provides better workability, sag resistance as well as appropriate setting time. Just 300 gms of 3X tile bonder is sufficient for 50 Kg cement bag.

Suitable for

- On-site mix for Tile Fixing

Technical Specifications

Packaging Size: 01 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	White Powder	> 20 Mins	> 10 Mins	≥ 0,5 Mpa	≥ 1.0 Mpa	2.0-2.5 sq. ft.	Type-4	C2 TE S2

Hydro-Seal Putty



This product increase Hydrophobicity and Water Resistance when mixed with the white putty. The additive boosts the performance of the putty and improves the longevity of the Paint. Suitable Floor: This product can be added with putty and applied on interior and exterior walls.

Suitable for

- Interior walls
- High-traffic areas
- Industrial environments
- Healthcare facilities
- Educational institutions

Technical Specifications

Packaging Size: 20 kg Bucket

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 1015-11
Specifications	Grey / White powder	3.0-3.5	>30 mins.	≥1.0 N/mm ²	1.50 Mpa	30-35 Sq.Ft	Type-3	3.5-7.5

Plaster Booster



This is an admixture in a powder form which reduces shrinkage in cement-based mortar. The stabilizer of the admixture provides homogeneity, counteracts intrinsic shrinkage and settling characteristics while the plasticizer helps to achieve high workability. It also increases the coverage of the plaster by reducing the rebound loss.

Suitable for

- 3X Water Resistance,
- Better Bonding,
- Active German Polymer Silicon
- Increase Whiteness

Technical Specifications

Packaging Size: 01 kg Bag

Parameters	Appearance	Pot life	Open time	Tensile Adhesion (28 days)	Shear Adhesion (28 days)	Coverage (20 kg bag)	IS 15477:2019	EN 12004
Specifications	Grey / White powder	>60 mins	>30 mins.	1.50 Mpa	1.50 Mpa	30-35 Sq.Ft	Type-3	C2 TE S1



ADHESIVES, WATERPROOFING, CHEMICAL PRODUCTS FOR BUILDING



Shuvidha Shanti , Nagar,
Mira Road (E), Mumbai – 401107



+91 892 883 1711
+91 22 3550 3983



Info@ustindustech.com
www.ustindustech.com